Smart Office IP Phone

ES206

ESCENE ES206 is a smart office IP phone with rich features. It has 128*64 HD graphic LCD up to 4-line display; it also has HD Sound Quality, unique art design, demountable bracket to provide multi-angle, 13 programmable keys, and friendly user interface to satisfy communication needs from users.

Key Features:

- Support 2 lines;
- Support demountable bracket to provide multi-angle;
- Support 13 programmable keys;
- Support Multi-language,e.g:Chinese,English,French,Russian,Italian and etc.
- 2*10/100M Ethernet ports,support POE；
- Auto-provision, HTTP/TFTP/FTP, TR069, PNP;

ES206 Technical Datasheet

Phone Features

2 SIP accounts, Hot line
Call hold, Call waiting, Call forward, Call return; Call transfer (blind/busy/ask)
Caller ID display, Redial, Mute, DND
Auto-answer, 3-way conferencing
Speed dial, SMS, Voicemail
Tone scheme, Volume control
Direct IP call without SIP proxy
Ring tone selection/import/delete
Black list, Hand-free indicator.
Call history: dialed/received/missed (50 -entries);
Soft keys programmable, Supports PC control
Multi-Language:
Chinese,English,French,Russian,Italian,Polish, Portuguesa,Portuguesa-Brasil,Spanish,Turkish

Advanced Features

13 programmable keys
XML Phone Book search and input & output
Enterprise phone book(800 entries)
LDAP phone book

IP PBX System Integration

Busy lamp field (BLF), BLF list
Bridged line appearance (BLA)
DND & Forward synchronization
Intercom, Paging, Music on hold
Call pickup, Dial Plan, Call recording
Anonymous call, Anonymous call rejection
Network conference, Distinctive ring tone

Codes and Voice Features

Wideband Codec: G.722
Narrowband codec: G.711μ/A, G.723.1
G.726, G.729AB,iLBC
VAD, CNG, AEC, AGC
Full-duplex,

Security

LLDP, VPN(L2TP) ,802.1x
Transport Layer Security (TLS)
Digest authentication using MD5/MD5-sess
Secure configuration file via AES encryption
Phone lock for personal privacy protection
Admin/User 2-level configuration mode

Network Features

SIP v1 (RFC2543), v2 (RFC3261)
DNS SRV (RFC3263); IPv6
NAT Traversal: STUN mode
DTMF: In-Band, RFC2833, SIP Info, Auto
HTTP/HTTPS Web Management
IP Assignment: Static/DHCP/PPPoE
Bridge/Router mode for PC port
TFTP/DHCP/PPPoE client
DNS client, NAT/DHCP server

Management

Auto-provision via FTP/TFTP/HTTP/HTTPS;
PNP; SNMP V1/2 , TR069 optional
Configuration:
browser/phone/auto-provision
Trace package and system log export

Physical Features

128*64 graphic LCD, Backlight
33 keys, including 13 programmable keys,
3 LEDs: 2* account lights, 1*status light
1* RJ-9 handset port
1*RJ-9 headset port(Option)
1*PSTN port(Option)
2xRJ45 10/100M Ethernet ports
Power adapter: AC 100~240V input and DC 5V/1A output
Power over Ethernet ,IEEE 802.3af,class 0(Option)
Power consumption: 1.5W
Net weight: 0.62kg
Dimension: 213*157*39mm
Operating humidity: 10~95%
Storage temperature: up to 60°C

Package Features

Qty/CTN: 10 PCS
N.W/CTN: 6.2kg
G.W/CTN: 8.5kg
Carton Meas: 430x345x250mm

Certifications

RoHS CE FC ISO 9001

Compatible with the platform

AVAYA, Alcatel-Lucent, Asterisk, BROADSOFT, elastix, GENESYS, HUAWEI, Metaswitch, NEC, Yeastar, ZTE中兴, 3CX

ESCENE Communication starts from SayHi™

Escene Communication Co.,Ltd

Address: Floor 4 Building C YueAn Industrial Park No.51
Huangcun Road Tianhe District, Guangzhou, China.
Postal Code: 510665